

L-Series PELICAN dredge with diesel power

Dredge pump: Metso LU40 ladder mounted pump, 12" x 12", 3-vane impeller

Dynamic Head Tank

Main Power Unit: Caterpillar C27, 880 horsepower

Accessory Power Unit: Caterpillar C15, 440 horsepower

Fuel Storage: 3,600 gallon

Water System: 2,500 gpm total flow from turbine pump

2.000 gpm for water nozzles 500 gpm for service water

Dredge Pump Drive: 90 degree direct drive gearbox reduction and Torqueshaft

Flotation: Center: Rectangular, 3/8" plate with watertight bulkheads

Side: Cylindrical, 3/8" plate with watertight bulkheads

Ladder: STIFF truss frame

180' overall length, 150' maximum mining depth

Hydraulic system: Constant flow pumps, 300 gallon reservoir with proportional controls

and oil/air cooling

Cutter: 9" pitch linear cutter

30,000 pound maximum digging force

Dynamic Head Tank

Rigging: 2 each M75 hoist winches with 1 x 24 BRUTE rigging blocks

Positioning: 3-wire. 3 each M18 positioning winches with Mini-MOAB blocks and NOMAD fairlead

Operators Cab: Elevated, 10' x 7', insulated, tinted windows, AC/heat, CONVAC S4, LADDERVAC II, velocity

meter, infinitely adjustable position for controls and seat

Dimensions: Overall length: 216'

Overall width: 30'

Displacement: 346,000 pounds

TWINKLE CO

TWINKLE CO

West Liberty, IA

319 627 6655 • twinkleco.com